

## Lifting stati. Aqualift F XL 200l Duo, SPF 4500-S3



### Article information

Item no.: 11060  
GTIN: 4026092057278  
Price group: 50

### Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

### Description

The lifting station for faecal and faecal-free wastewater is equipped with a submersible pump and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

The station is controlled by a user-friendly control unit, which can be optionally integrated in the building management system via a potential-free contact or alarm and collective fault messages can be output via a GSM interface (Comfort control unit).

Type of wastewater: wastewater with sewage  
Installation situation: free-standing set-up

### Version:

Type of system: Twin pump station

### General characteristics:

Colour: black  
Standard: EN 12050-1

### Tank:

Tank volume: 200 l  
Pressure pipe connection: vertical

**Pumping device:**

|  |                     |
|--|---------------------|
| Pump:  | SPF 4500            |
| Number of pumps:                               | 2                   |
| Operating mode:                                | S3 - 50 %           |
| Type of fuse required (electrical protection): | 3 x C 25 A          |
| Impeller type:                                 | Multi-vane impeller |
| Length of mains cable for pump:                | 5 m                 |

**Control:**

|                               |                |
|-------------------------------|----------------|
| Control unit:                 | Comfort        |
| Operating voltage:            | 400 V          |
| Mains frequency:              | 50 Hz          |
| Type of level measurement:    | pneumatic      |
| Level measurement instrument: | Immersion pipe |