


Submersible pump Aquadive KTP 300 without float switch, 10 m



Article information

Item no.: 28740
 GTIN: 4026092000908
 Price group: 20

Description

KTP 300 submersible pump without float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Type of wastewater: wastewater without sewage

General characteristics:

Material: Polymer
 Standard: EN 12050-2

Dimensions:

Length: 275 mm
 Width: 390 mm
 Height: 216 mm

Pressure pipe connection: R 1"
 Free passage: 10 mm

Pumping device:

Pump: KTP 300
 Number of pumps: 1

| | |
|--|--------------------------------|
| Max. pumping capacity: | 8 m ³ /h |
| Max. pumping height: | 6 m |
| Operating voltage: | 230 V |
| Mains frequency: | 50 Hz |
| Operating mode: | S1 |
| Power P1: | 0.34 kW |
| Power P2: | 0.21 kW |
| Speed: | 2,800 U/min |
| Type of fuse required (electrical protection): | C 16 A |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Connection type: | Schuko (earthed contact) 2-pin |
| Weight: | 4 kg |
| Impeller type: | Multi-vane impeller |
| Length of mains cable for pump: | 10 m |
| Rated current: | 1.6 A |
| Protection class (pump): | IP 68 (3m) |
| Protection class: | I |
| Type of pump connection cable: | H07RN-F 3G 1.0 mm ² |
| Temperature monitoring: | integrated |
| Insulation class: | F |
| Cable length: | 10 m |