

## Practicus basement drain DN 100, Black grating, Horizontal outlet



### Article information

Item no.: 34101  
GTIN: 4026092007884  
Price group: 10

### Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

### Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

### Version:

Odour trap: no

### General characteristics:

Nominal size (DN): 100  
Outer diameter (OD): 110  
Standard: EN 1253-2

### Dimensions:

Length: 188 mm  
Width: 150 mm  
Cutout dimension, length: 220 mm  
Cutout dimension, width: 180 mm

### Tank:

Number of outlets: 1 ST  
Installation depth: 152 - 208 mm

### Drain body:

Material of drain body: Polymer

|                      |                                     |
|----------------------|-------------------------------------|
| Socket version:      | lateral                             |
| Vertical adjustment: | vertically adjustable upper section |

#### Coverage features:

|                  |                 |
|------------------|-----------------|
| Type of cover:   | Slotted cover   |
| Cover material:  | Polymer         |
| Colour of cover: | black           |
| Load class:      | K 3 (EN 1253-1) |
| Length:          | 138 mm          |
| Width:           | 138 mm          |
| Surface:         | Polished SST    |
| Sludge bucket:   | yes             |
| Locking:         | placed          |

#### Grating:

|                                            |         |
|--------------------------------------------|---------|
| Rim material:                              | Polymer |
| Shape of upper section:                    | square  |
| Upper section material:                    | Polymer |
| Discharge rate (l/s) with 10 mm backwater: | 1,1 l/s |
| Discharge rate (l/s) with 20 mm backwater: | 1.8 l/s |