

Classic bathroom drain, upper section for combined waterproofing Gl fl., DN 70, horiz., Slotted grating, K3



Article information

Item no.: 40179.50
GTIN: 4026092029428
Price group: 10

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Version:

Odour trap:	included
Type of waterproofing layer:	Waterproofing layer
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Adhesive flange (suitable for moisture barriers)
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	50 mm

General characteristics:

Nominal size (DN):	70
Outer diameter (OD):	75
Standard:	EN 1253-1

Dimensions:

Length:	332 mm
Width:	332 mm
Cutout dimension, length:	350 mm
Cutout dimension, width:	350 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: ABS
Socket version: lateral

Vertical adjustment: vertically adjustable upper section
Vertical adjustment: 55 - 120 mm

Coverage features:

Type of cover: Slotted cover
Cover material: 304 stainless steel
Colour of cover: silver
Load class: K 3 (EN 1253-1)
Length: 95 mm
Width: 95 mm
Locking: placed

Grating:

Rim length: 132 mm
Rim width: 132 mm
Rim material: ABS

Upper section material: ABS
Discharge rate (l/s) with 20 mm backwater: 0.8 l/s