

Classic bathroom drain, upper section for combined waterproofing DN 50, vert., Slotted grating, L 15



Article information

Item no.: 40250.51
GTIN: 4026092028582
Price group: 10

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Version:

Odour trap:	included
Type of waterproofing layer:	Waterproofing layer
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	50 mm

General characteristics:

Nominal size (DN):	50
Outer diameter (OD):	50
Standard:	EN 1253-1

Dimensions:

Length:	312 mm
Width:	312 mm
Cutout dimension, length:	220 mm
Cutout dimension, width:	180 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: ABS
Socket version: vertical

Vertical adjustment: vertically adjustable upper section
Vertical adjustment: 45 - 110 mm

Coverage features:

Type of cover: Slotted cover
Cover material: 304 stainless steel
Colour of cover: silver
Load class: L 15 (EN 1253-1)
Length: 138 mm
Width: 138 mm
Surface: Polished SST
Locking: placed

Grating:

Rim length: 150 mm
Rim width: 150 mm
Rim material: 304 stainless steel

Shape of upper section: square
Upper section material: ABS
Discharge rate (l/s) with 20 mm backwater: 0.8 l/s