

## Practicus drain body Press. fl., DN 50, Vertical outlet



### Article information

Item no.: 45259  
 GTIN: 4026092033807  
 Price group: 10

### Advantages

- Hygiene: hygienic,
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute

### Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover.

The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals.

### Version:

System:	125
Odour trap:	included
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
Sealing water height:	50 mm

### General characteristics:

Nominal size (DN):	50
Outer diameter (OD):	50

**Dimensions:**

Height: 207 mm  
Diameter: 273 mm

**Tank:**

Number of outlets: 1 ST

**Drain body:**

Material of drain body: PP  
Socket version: vertical