


Roof drain Ecoguss Press. fl., DN 100, with leaf trap



Article information

Item no.: 45950
GTIN: 4026092001318
Price group: 10

Advantages

- Made of recyclable composite
- Permanently corrosion-free surface

Description

The roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap.

The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

Version:

System:	100
Type of waterproofing layer:	single waterproofing layer
Heating:	without
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)

General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110

Dimensions:

Length:	246 mm
---------	--------

Width:	246 mm
Height:	182 mm
Cutout dimension, length:	180 mm
Cutout dimension, width:	180 mm
Diameter:	120 mm

Drain body:

Material of drain body:	PP
-------------------------	----

Coverage features:

Type of cover:	Leaf trap
Cover material:	Polymer
Colour of cover:	black
Length:	120 mm
Width:	120 mm
Height:	80 mm

Shape of upper section:	round
Upper section material:	PP