


Roof drain for flat roof surfaces Double press fl., DN 100, with leaf trap



Article information

Item no.: 45970
 GTIN: 4026092029718
 Price group: 10

Advantages

- Made of recyclable composite
- Permanently corrosion-free surface

Description

The Ecoguss roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap.

The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. Separate equipotential bonding is not necessary.

Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

Version:

System:	100
Type of waterproofing layer:	double pressure sealing flange
Heating:	without
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)

General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110

Dimensions:

Length:	246 mm
Width:	246 mm
Cutout dimension, length:	180 mm
Cutout dimension, width:	180 mm
Diameter:	120 mm

Drain body:

Material of drain body:	PP
Vertical adjustment:	vertically adjustable upper section
Vertical adjustment:	40 - 80 mm

Coverage features:

Type of cover:	Leaf trap
Cover material:	Polymer
Colour of cover:	black
Length:	120 mm
Width:	120 mm
Height:	80 mm
Upper section material:	PP