

Upper section, Linearis Compact L: 1050 mm, Sys 100, 304 SST cover, K 3



Article information

Item no.: 47811S GTIN: 4026092079959 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

Version:

System: Odour trap: Type of waterproofing layer: Seepage opening:	100 included Waterproofing layer yes
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	50 mm
General characteristics:	
Nominal size (DN):	100 100
Outer diameter (OD):	100
Dimensions:	
Width: Height:	136 mm 77 mm
null:	1,115 mm



Coverage features:

Type of cover: Grating design: Cover material: Colour of cover: Load class: Locking:

Stainless steel cover optionally tileable 304 stainless steel silver, selectable K 3 (EN 1253-1) placed

1,050 mm

304 stainless steel

66 mm

ABS

0.6 l/s

0.5 l/s

Grating:

Rim length: Rim width: Rim material:

Upper section material: Discharge rate (l/s) with 10 mm backwater: Discharge rate (l/s) without backwater:

Page 2