

Upper section, Linearis Compact L: 1150 mm, Sys 100, 304 SST cover, K 3



Article information

Item no.: 47812S

GTIN: 4026092079942

Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

Version:

System: 100 Odour trap: included

Type of waterproofing layer: Waterproofing layer

Seepage opening: yes

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 50 mm

General characteristics:

Nominal size (DN): 100 Outer diameter (OD): 100

Dimensions:

Width: 136 mm Height: 77 mm null: 1,215 mm



Coverage features:

Type of cover:
Grating design:
Cover material:
Colour of cover:
Load class:

Stainless steel cover optionally tileable
304 stainless steel
silver, selectable
K 3 (EN 1253-1)

Locking: placed

Grating:

Rim length: 1,150 mm Rim width: 66 mm

Rim material: 304 stainless steel

Upper section material:

Discharge rate (l/s) with 10 mm backwater:

Discharge rate (l/s) without backwater:

0.6 l/s

0.5 l/s