

## Roof drain Ecoguss Press. fl., waterproof concrete, DN 70, without heating



### Article information

Item no.: 48370.01  
GTIN: 4026092039335  
Price group: 40

### Advantages

- Made of recyclable composite
- Permanently corrosion-free surface

### Description

The Ecoguss roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap.

The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. Separate equipotential bonding is not necessary.

### Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

### Version:

System:	200
Type of waterproofing layer:	double waterproofing layer in waterproof concrete
Heating:	without

Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
--	---

### General characteristics:

Nominal size (DN):	70
Outer diameter (OD):	78
Standard:	EN 1253, DIN 1986-100

**Dimensions:**

Length:	365 mm
Width:	365 mm
Cutout dimension, length:	227 mm
Cutout dimension, width:	227 mm
Diameter:	365 mm

**Drain body:**

Material of drain body:	Ecoguss
Vertical adjustment:	vertically adjustable upper section
Vertical adjustment:	40 - 140 mm

**Coverage features:**

Type of cover:	Gravel trap
Cover material:	Polymer
Colour of cover:	black
Upper section material:	Ecoguss