

## Parking deck drain, Ecoguss DN 125, square, Connection polymer pipe



### Article information

Item no.: 48502  
GTIN: 4026092036112  
Price group: 40

### Advantages

- Breakproof & load resistant
- Fulfills highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

### Description

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket.

The recyclable composite material Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

Separate equipotential bonding is not necessary.

### Version:

|                                        |                   |
|----------------------------------------|-------------------|
| System:                                | 125               |
| Waterproofing layer on the drain body: | Connection flange |

### General characteristics:

|                      |           |
|----------------------|-----------|
| Nominal size (DN):   | 125       |
| Outer diameter (OD): | 125       |
| Standard:            | EN 1253-2 |

### Dimensions:

|         |        |
|---------|--------|
| Length: | 290 mm |
| Width:  | 290 mm |
| Height: | 196 mm |

|                           |        |
|---------------------------|--------|
| Cutout dimension, length: | 300 mm |
| Cutout dimension, width:  | 300 mm |

#### Coverage features:

|                  |                     |
|------------------|---------------------|
| Type of cover:   | Round slotted cover |
| Cover material:  | Ecoguss             |
| Colour of cover: | black               |
| Load class:      | B 125 (EN 124)      |
| Length:          | 234 mm              |
| Width:           | 234 mm              |
| Surface:         | EDM                 |
| Sludge bucket:   | yes                 |
| Locking:         | Lock & Lift         |

#### Grating:

|               |         |
|---------------|---------|
| Rim length:   | 247 mm  |
| Rim width:    | 247 mm  |
| Rim material: | Ecoguss |

|                                            |         |
|--------------------------------------------|---------|
| Shape of upper section:                    | square  |
| Upper section material:                    | Ecoguss |
| Discharge rate (l/s) with 20 mm backwater: | 4.5 l/s |