

Linearis Comfort upper section L: 750 mm, System 125, WaD, K 3



Article information

Item no.: 48928M GTIN: 4026092079041 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

Version:

| System: | 125 |
|---|--|
| Odour trap: | included |
| Type of waterproofing layer: | Waterproofing layer |
| Seepage opening: | open |
| Waterproofing layer on the upper section: | Factory-fitted sealing collar (WaD) according to DIN |
| Water exposure class in accordance to DIN | 18534 |
| 18534-1 (up to and including): | W3-I |
| Sealing water height: | 50 mm |
| General characteristics: Nominal size (DN): Outer diameter (OD): | 125 125 |
| Dimensions: | |
| Width: | 243 mm |
| Height: | 110 mm |
| null: | 815 mm |



Coverage features:

Type of cover: Grating design: Cover material: Colour of cover: Load class: Locking: Stainless steel cover optionally tileable 304 stainless steel silver, selectable K 3 (EN 1253-1) placed

Grating:

| Rim length: | 750 mm |
|-------------------------|---------------------|
| Rim width: | 66 mm |
| Rim material: | 304 stainless steel |
| | |
| Upper section material: | ABS |

Discharge rate (l/s) with 10 mm backwater: Discharge rate (l/s) without backwater: ABS 1.1 l/s 1 l/s