


Linearis Comfort upper section L: 1050 mm, System 125, WaD, K 3



Article information

Item no.: 48931M
 GTIN: 4026092079072
 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

Version:

| | |
|--|--|
| System: | 125 |
| Odour trap: | included |
| Type of waterproofing layer: | Waterproofing layer |
| Seepage opening: | open |
| Waterproofing layer on the upper section: | Factory-fitted sealing collar (WaD) according to DIN 18534 |
| Water exposure class in accordance to DIN 18534-1 (up to and including): | W3-I |
| Sealing water height: | 50 mm |

General characteristics:

| | |
|----------------------|-----|
| Nominal size (DN): | 125 |
| Outer diameter (OD): | 125 |

Dimensions:

| | |
|---------|----------|
| Width: | 243 mm |
| Height: | 115 mm |
| null: | 1,115 mm |

Coverage features:

| | |
|------------------|-----------------------|
| Type of cover: | Stainless steel cover |
| Grating design: | optionally tileable |
| Cover material: | 304 stainless steel |
| Colour of cover: | silver, selectable |
| Load class: | K 3 (EN 1253-1) |
| Surface: | Brushed SST |
| Locking: | placed |

Grating:

| | |
|--|---------------------|
| Rim length: | 1,050 mm |
| Rim width: | 66 mm |
| Rim material: | 304 stainless steel |
| Shape of upper section: | square |
| Upper section material: | ABS |
| Discharge rate (l/s) with 10 mm backwater: | 1.1 l/s |
| Discharge rate (l/s) without backwater: | 1 l/s |