


## Light liquid trap DN 100, Slotted grating, with backwater protection



### Article information

Item no.: 52101  
 GTIN: 4026092029770  
 Price group: 10

### Advantages

- Blocks the path of light liquids in the event of an accident/emergency
- Including odour trap

### Description

The light liquid trap made of polymer is suitable for floor slab installation and is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

### Version:

Odour trap:	included
Sealing water height:	50 mm
Backwater protection:	Type 5
Number of mechanical backwater flaps:	2

### General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110
Standard:	EN 1253-3, EN 1253-5, EN 13564

### Dimensions:

Length:	320 mm
Width:	243 mm

Cutout dimension, length:	400 mm
Cutout dimension, width:	250 mm

#### **Tank:**

Installation depth:	216 - 276 mm
---------------------	--------------

#### **Drain body:**

Material of drain body:	Polymer
Vertical adjustment:	vertically adjustable upper section
Vertical adjustment:	30 - 90 mm

#### **Coverage features:**

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Load class:	K 3 (EN 1253-1)
Length:	188 mm
Width:	188 mm
Sludge bucket:	yes

#### **Grating:**

Rim length:	200 mm
Rim width:	200 mm
Upper section material:	Polymer
Discharge rate (l/s) with 20 mm backwater:	1 l/s