


## Ferrofix floor drain Sys 200, horiz., Ladd grt



### Article information

Item no.: 55350.30  
GTIN: 4026092009956  
Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel

### Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap, a lip seal and a temporary protective cover.

The outlet socket is suitable for connection to SML cast iron pipes.

#### Version:

System:	200
Odour trap:	included
Waterproofing layer on the upper section:	Connection flange
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	70 mm

#### General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110
Standard:	EN 1253-1

#### Dimensions:

Length:	280 mm
Width:	280 mm

#### Tank:

Number of outlets:	1 ST
--------------------	------

**Drain body:**

Material of drain body:	Stainless steel 14301
Socket version:	lateral
Vertical adjustment:	vertically adjustable upper section
Upper section:	vertically adjustable

**Coverage features:**

Type of cover:	Ladder grating
Cover material:	Stainless steel 14301
Load class:	M 125 (EN 1253-1)
Length:	190 mm
Width:	190 mm
Height:	30 mm
Locking:	unlocked

**Grating:**

Rim length:	200 mm
Rim width:	200 mm
Upper section material:	Stainless steel 14301