


## Ferrofix drain body Sys 200, Press. fl., Vertical outlet



### Article information

Item no.: 55600  
GTIN: 4026092007570  
Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- Variably combinable with upper sections

### Description

In combination with a System 200 upper section, the Ferrofix stainless steel drain body is used for point drainage and is equipped with a removable odour trap, a lip seal and a temporary protective cover.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes.

### Version:

System:	200
Odour trap:	included
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
Sealing water height:	70 mm

### General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110
Standard:	EN 1253-1

### Dimensions:

Length:	420 mm
Width:	420 mm

Height: 231 mm

**Tank:**

Number of outlets: 1 ST

**Drain body:**

Material of drain body: 304 stainless steel  
Socket version: vertical