


Ferrofix renovation drain GI fl., DN 50, horizontal, Slotted grating



Article information

Item no.: 59335
GTIN: 4026092103043
Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- ideal for the food industry
- catering kitchens and swimming pools
- Including odour trap

Description

The Ferrofix stainless steel renovation drain is equipped with a horizontal outlet DN 50 as well as a removable odour trap.

Version:

System: 125
Odour trap: included

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)
Sealing water height: 50 mm

General characteristics:

Nominal size (DN): 50
Outer diameter (OD): 50

Dimensions:

Length: 273 mm
Width: 248 mm
Height: 100 mm
Max. design height: 100 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: Stainless steel 14301
Socket version: lateral

Coverage features:

Type of cover: Slotted cover
Cover material: 304 stainless steel
Load class: K 3 (EN 1253-1)
Length: 138 mm
Width: 138 mm
Locking: screwed

Grating:

Rim length: 148 mm
Rim width: 148 mm

Upper section material: Stainless steel 14301
Discharge rate (l/s) with 20 mm backwater: 0.8 l/s