

Ecoguss yard drain System 100, vert., Slotted grating, B 125



Article information

Item no.: 67110B
 GTIN: 4026092039373
 Price group: 10

Advantages

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius
- Permanently corrosion-free surface

Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket.

The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Version:

| | |
|-------------|-----|
| System: | 100 |
| Odour trap: | no |

General characteristics:

| | |
|--------------------|-----|
| Nominal size (DN): | 100 |
|--------------------|-----|

Drain body:

| | |
|-----------------|----------|
| Socket version: | vertical |
|-----------------|----------|

Coverage features:

| | |
|----------------|---------------------|
| Type of cover: | Round slotted cover |
|----------------|---------------------|

| | |
|-------------------------|----------------|
| Cover material: | Ecoguss |
| Colour of cover: | black |
| Load class: | B 125 (EN 124) |
| Length: | 247 mm |
| Width: | 247 mm |
| Sludge bucket: | yes |
| Locking: | Lock & Lift |
| Shape of upper section: | square |