


Staufix clean out DN 125, Floor slab, black



Article information

Item no.: 700125.10S
 GTIN: 4026092075920
 Price group: 10

Advantages

- Simple conversion to Staufix type 1
- Type 2 or StaufixControl
- Fast
- toolless access for cleaning
- Own gradient only 8 mm

Description

The clean out for faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work.

Thanks to the modular KESSEL system, existing systems can easily be supplemented by up to two flaps and one emergency closure or be converted to the StaufixControl backwater valve.

Type of wastewater:

wastewater without sewage

Installation situation:

floor slab installation

Version:

Type of waterproofing layer:

Waterproofing layer

Delivery state:

Installation-ready (connection parts must be connected on site)

General characteristics:

Nominal size (DN):

125

Outer diameter (OD):

125

Colour:

black

Dimensions:

| | |
|---------------------------|--------|
| Length: | 511 mm |
| Width: | 444 mm |
| Cutout dimension, length: | 750 mm |
| Cutout dimension, width: | 750 mm |

Tank:

| | |
|--|-------------------------------------|
| Installation depth: | 341 - 464 mm |
| Groundwater resistant from lower edge of base section: | 3.000 mm |
| Vertical adjustment: | vertically adjustable upper section |

Coverage features:

| | |
|---|-------------------------|
| Type of cover: | Cover plate |
| Cover material: | Polymer |
| Colour of cover: | black |
| Load class: | L 15 (EN 1253-1) |
| Length: | 366 mm |
| Width: | 366 mm |
| Tightness: | surface water resistant |
| Locking: | Lock & Lift |
| Vertical drop between inlet and outlet: | 8 mm |