


Controlfix clean out DN 100, Floor slab, black





Article information

Item no.: 80100S

GTIN: 4026092004050

Price group: 30

Advantages

- Simple conversion to Staufix SWA
- Staufix FKA or Pumpfix F
- Fast
- toolless access for cleaning
- Available as a complete set or module set

Description

The Premium clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work.

Thanks to the modular KESSEL system, existing systems can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station.

Type of wastewater: wastewater with and without sewage

Installation situation: floor slab installation

Version:

Type of waterproofing layer: Waterproofing layer

Delivery state: Installation-ready (connection parts must be

connected on site)

General characteristics:

Nominal size (DN): 100
Outer diameter (OD): 110
Colour: black



_									
П	П	m	Ω	n	CI	ın	n	S	

Length:486 mmWidth:590 mmCutout dimension, length:750 mmCutout dimension, width:750 mm

Tank:

Installation depth: 486 - 640 mm Groundwater resistant from lower edge of base 3,000 mm

section:

Drain body:

Socket version: including spigot and socket

Vertical adjustment: vertically adjustable upper section

Coverage features:

Type of cover:

Cover plate
Cover material:

Polymer
Colour of cover:

black

Load class: L 15 (EN 1253-1)

Length: 366 mm Width: 366 mm

Tightness: surface water resistant

Locking: Lock & Lift

Vertical drop between inlet and outlet: 9 mm