


Chamber module LW 1000 ground Access LW 600, 3630-3879 mm, Class A/B



Article information

Item no.: 8740078
 GTIN: 4026092065938
 Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm
- Vertically adjustable upper section available in LW 600 and LW 800 from class K 3 to class D
- ideal for scoring up to DN 150
- lift-protected

Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities.

Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

Installation situation: underground installation

Version:

Note on installation depth: note maximum installation depth 5000 mm in combination with technical module

Delivery state: Partly for on-site assembly (access steps have been pre-mounted in the factory)

General characteristics:

Colour:	black
Standard:	EN 13598-2
Approval:	Z-42.1-527

Dimensions:

Length:	1,200 mm
Width:	1,200 mm

Tank:

Inlet max. scoring (DN):	150 mm
Installation depth:	3,630 - 3,897 mm
Groundwater resistant from lower edge of base section:	3,000 mm
Clear width of tank (LW):	1,000 mm
Clear width of entry (LW):	600 mm
Vertical adjustment:	vertically adjustable upper section

Coverage features:

Type of cover:	Round cover plate
Cover material:	Grey iron
Colour of cover:	black
Load class:	B 125 (EN 124)
Length:	648 mm
Width:	648 mm
Height:	95 mm
Tightness:	surface water resistant
Surface:	Grey iron
Locking:	unlocked