

## Sampling chamber DN 200, Class D



### Article information

Item no.: 915883D  
GTIN: 4026092048573  
Price group: 60

### Description

Sampling chamber LW 450 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length.

Flow direction: straight

A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL AG.

### General characteristics:

Material: PE  
Colour: black

### Dimensions:

Length: 730 mm

### Tank:

Inlet nominal size (DN): 200 mm  
Inlet nominal size (OD): 200 mm  
Outlet nominal size (DN): 200 mm  
Outlet nominal size (OD): 200 mm  
Distance pipe bottom inlet to tank bottom: 205 mm  
Installation depth: 450 - 1300 mm  
Clear width of tank (LW): 450

Vertical adjustment: vertically adjustable upper section

**Coverage features:**

|   |   |
|---|---|
| Type of cover:                          | Cover plate                             |
| Cover material:                         | Grey iron                               |
| Colour of cover:                        | black                                   |
| Load class:                             | D 400 (EN 124)                          |
| Tightness:                              | odour-tight and surface water resistant |
| Vertical drop between inlet and outlet: | 160 mm                                  |