


Grease separator EasyClean ground NS 2, Direct, 550-950 mm, A/B, right





Article information

Item no.: 93002.80B-DR GTIN: 4026092095065

Price group: 60

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via one or several service access covers.

A direct disposal pipe socket is available for odour-reduced manual disposal.

A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL AG.

20 year polyethylene warranty.

Installation situation: underground installation

Version:

Type of disposal: manual
Disposal system: Disposal pipe
Disposal variant: Direct
Nominal size (NS): 2

Load-bearing capacity (DIN 19901): E2

Note on installation depth: Installation in the ground, frost-free depth 800 mm



Delivery state:	Installation-ready (connection parts must be connected on site)
General characteristics:	
Material:	PE
Dimensions:	
Length: Width: Diameter:	1,380 mm 1,106 mm 1,106 mm
Tank:	
Inlet nominal size (DN): Outlet nominal size (DN): Distance pipe bottom inlet to tank bottom: Distance pipe bottom outlet to tank bottom: Installation depth: Groundwater resistant from lower edge of base section: Clear width of entry (LW): Connection inlet/outlet sockets:	100 100 860 mm 790 mm 550 - 900 mm 500 mm 600 mm PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Coverage features:	
Type of cover: Cover material: Colour of cover: Load class: Tightness:	Cover plate Grey iron black B 125 (EN 124) odour-tight and surface water resistant
Wastewater contents:	
Separator contents: Contents of sludge trap: Storage quantity of grease: Storage quantity of light liquid:	370 l 200 l 120 l 120 l