

Grease separat. EasyClean Modular free, NS 4, Standard, 2-part

Article information

Item no.: 93004-R
GTIN: 4026092071236
Price group: 60

Advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

| | |
|---|---|
| Type of disposal: | manual with suction hose |
| Disposal variant: | Standard |
| Refill inlet in accordance with DIN 1988: | no |
| Nominal size (NS): | 4 |
| Inspection window: | no |
| Shredder-Mix-System: | no |
| SonicControl: | no |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

General characteristics:

Material: PE

Dimensions:

| | |
|-------------------------------|----------|
| Set-up area, height: | 1,620 mm |
| Required access area, length: | 1,400 mm |

| | |
|--|----------|
| Required access area, width: | 1,300 mm |
| Required access area, height: | 790 mm |
| Height tank bottom up to centre section: | 765 mm |
| Height centre section to top edge of tank: | 790 mm |

Tank:

| | |
|---|---|
| Inlet nominal size (DN): | 100 |
| Inlet nominal size (OD): | 110 mm |
| Outlet nominal size (DN): | 100 |
| Outlet nominal size (OD): | 110 mm |
| Distance pipe bottom inlet to tank bottom: | 1,160 mm |
| Distance pipe bottom outlet to tank bottom: | 1,090 mm |
| Chamber system: | two-piece chamber |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

Coverage features:

| | |
|------------------|-----------------------|
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Tightness: | odour-tight |
| Locking: | Quick-release closure |

Wastewater contents:

| | |
|-----------------------------|-------|
| Separator contents: | 560 l |
| Total volume: | 960 l |
| Contents of sludge trap: | 400 l |
| Storage quantity of grease: | 160 l |

Control:

| | |
|---------------|----|
| Control unit: | no |
|---------------|----|