


EasySink sediment separator free, NS 2



Article information

Item no.: 97202/000
GTIN: 4026092026885
Price group: 60

Advantages

- Waterproof and resistant to aggressive wastewater
- Odour-tight tank
- Low-maintenance operation

Description

The sediment separator is suitable for exposed installation in frost-protected rooms. The collection tank is equipped with a removable sediment tank (NS 2 with two sediment tanks) both made of permanently resistant polymer (PE). An odour trap is installed in the outlet. An odour-tight cover with quick-release closure makes easy access possible for cleaning and maintenance work.

20 year polyethylene warranty.
Installation situation:

free-standing set-up

Version:

Type of disposal:
Odour trap:
Nominal size (NS):

manual with suction hose
included
2

Delivery state:

Installation-ready (connection parts must be connected on site)

General characteristics:

Material:

PE

Dimensions:

Set-up area, length: 985 mm
Set-up area, width: 650 mm
Set-up area, height: 598 mm
Required access area, length: 800 mm

Required access area, width: 650 mm

Tank:

Inlet nominal size (DN): 70
Inlet nominal size (OD): 75 mm
Outlet nominal size (DN): 70
Outlet nominal size (OD): 75 mm
Distance pipe bottom inlet to tank bottom: 373 mm
Distance pipe bottom outlet to tank bottom: 255 mm
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS

Coverage features:

Type of cover: Cover
Cover material: Polymer
Colour of cover: black
Length: 630 mm
Width: 630 mm
Tightness: odour-tight
Locking: Quick-release closure

Control:

Control unit: no
Volume of collecting tank: 51 l