

Accessories

Closure valves		Outer diameter Ø (mm)	Art. no.
Closure valve, vertical	<p>Compatibility: For lifting station <i>Aqualift F Basic</i>, <i>Aqualift F Mono / Duo</i> and <i>Aqualift F XL</i></p> <p>Function: For the pressure pipe of KESSEL lifting stations with plastic fitting; for connection to pressure pipe, a KESSEL flange connector or adapter is required.</p> <p>Inclusive: Gasket, screw</p>	Ø 90	28 715
Closure valve with flange adaptor, vertical	<p>Compatibility: For lifting station <i>Aqualift F Basic</i>, <i>Aqualift F Mono / Duo</i> and <i>Aqualift F XL</i></p> <p>Function: For the pressure pipe of KESSEL lifting stations with plastic fitting</p> <p>Inclusive: With screwed flange adaptor, for connection to a standard flange DN 80 according to DIN 2501 (without sealing gasket and screw)</p>	Ø 90	28 716
Closure valve	<p>Compatibility: With lateral pressure pipe for lifting stations <i>Aqualift F</i></p>	Ø 90 Ø 110	28 682 28 683
	<p>Compatibility: For installation on the inlet side (no pressure) for lifting stations <i>Aqualift F</i></p>	Ø 110 Ø 160	28 698 28 699
Connection flange		Outer diameter Ø (mm)	Art. no.
in PE	<p>Compatibility: For KESSEL plastic fittings; for lifting station <i>Aqualift F XL</i></p>	Ø 90	28 713
	<p>Compatibility: For KESSEL plastic fittings; for <i>Aqualift F Basic</i> and <i>Aqualift F XL</i>; also in combination with closure valve Art. no. 28 715</p> <p>Function: Spigot end for DN 100 pressure pipe connection</p>	Ø 110	28 712
Manual diaphragm pump 1 1/2 inch			Art. no.
Manual diaphragm pump in cast iron	<p>Compatibility: For manually pumping wastewater; for lifting station <i>Aqualift F Mono / Duo</i> and <i>Aqualift F XL</i></p> <p>Inclusive: With a ball valve on inlet and outlet side</p>		28 680
Flange adaptor		Outer diameter Ø (mm)	Art. no.
in PE	<p>Compatibility: From KESSEL fitting to standard flange; for lifting station <i>Aqualift F XL</i></p>	DN 80	28 714
in cast iron	<p>Compatibility: For use with cast iron pressure pipes; for lifting station <i>Aqualift F XL</i></p> <p>Function: Adaptor from DN 80 to DN 100</p> <p>Inclusive: Flange according to DIN 2501</p>	-	28 068