228 **4.1 Bathroom drains** Catalogue EN 4.2 **KESSEL AG** 

## Scada without LED-backlighting

Matrix order system


## Drain body | Co

Wall drain Scada
For floor drainage indoors
With odour trap and flange
for alternative sealing.
Drainage capacity 0.5 l/sec flow rate
Sealing water height 22 mm
Drain body in ABS,
lateral outlet Ø 50, with factorymounted waterproofing membrane.
Connection option at the front,
on the left side or right side.

## Covers

Cover Scada in stainless steel AISI 304

Invisible		Wave	
with stainless steel	Width×height	Width×height	Width×height
frame AISI 304	312×74 mm	312×74 mm	312×67 mm
Width×height	For floor tiles	For floor tiles	For floor tiles
296×61 mm	up to 10 mm	up to 10 mm	up to 17 mm
For floor tiles up			
to 10 mm, can be			
tiled with wall tiles			
up to 10 mm			
Art. no. 48 011	Art. no. 48 012	Art. no. 48 013	Art. no. 48 014



H1 = Upper edge flange 65 - 200 mm H2 = Upper edge tile 80 - 215 mm

H3 = Overall height 218 - 353 mm (incl. installation supports)

Art. no. 48 000M

Item comprised of drain body Scada and drain cover

	Art. no.	48 000.01M	Art. no.	48 000.02M	Art. no.	48 000.03M	Art. no.	48 000.04M

System 125

## **Accessories**

Scada

Drywall mount		Height×width in mm	Art. no.
Drywall mount	Compatibility: For drain body Scada Inclusive: Adhesive	300×623	48 063