

Ecoguss with glue flange

Matrix order system

System 125



Drain body

Ecoguss resistant with glue flange


for connection to SML-pipe, with odour trap.
 Drainage capacity in l/sec with 20 mm / 10 mm threshold see table.
 Sealing water height 50 mm

Modular system
 see pages 244 – 245

Upper sections


Shallow bed upper section in ABS
 with included waterproofing membrane

Slotted cover
 138×138 mm and rim in stainless steel AISI 304, class K 3, screwed



Art. no. 48 963


Design cover Kessel
 120×120 mm and rim in stainless steel AISI 304, class L 15, Lock & Lift locking system



Art. no. 48 904


Upper section in ABS

Design cover Kessel
 120×120 mm and rim in stainless steel AISI 304, class L 15, Lock & Lift locking system




Art. no. 48 201

Slotted cover
 138×138 mm in stainless steel AISI 304, class K 3, screwed



Art. no. 48 950

Drain body with lateral outlet



Ø	H	B
58	120	245
78	107	134
83	106	134
110	90	148

Ø 58 Art. no. 48 558

Ø 78 Art. no. 48 578


Ø 83 Art. no. 48 583

Ø 110 Art. no. 48 511

Complete drain comprising a combination of the upper section and drain body

Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
48 558.51	48 558.53	48 558.63	48 558.11	48 558.11
Drainage capacity* 1.6 / 1.3	Drainage capacity* 1.5 / 1.2	Drainage capacity* 1.4 / 1.0	Drainage capacity* 1.4 / 1.0	Drainage capacity* 1.4 / 1.0
48 578.51	48 578.53	48 578.63	48 578.11	48 578.11
Drainage capacity* 1.6 / 1.2	Drainage capacity* 1.5 / 1.2	Drainage capacity* 1.4 / 1.1	Drainage capacity* 1.4 / 1.1	Drainage capacity* 1.4 / 1.1
48 583.51	48 583.53	48 583.63	48 583.11	48 583.11
Drainage capacity* 1.6 / 1.2	Drainage capacity* 1.5 / 1.2	Drainage capacity* 1.4 / 1.1	Drainage capacity* 1.4 / 1.1	Drainage capacity* 1.4 / 1.1
48 511.51	48 511.53	48 511.63	48 511.11	48 511.11
Drainage capacity* 1.8 / 1.0	Drainage capacity* 1.8 / 1.0	Drainage capacity* 1.6 / 1.0	Drainage capacity* 1.6 / 1.0	Drainage capacity* 1.6 / 1.0

Drain body with vertical outlet



Ø	H
58	100
78	110
83	110
110	110

Ø 58 Art. no. 48 658

Ø 78 Art. no. 48 678

Ø 83 Art. no. 48 683

Ø 110 Art. no. 48 611

Complete drain comprising a combination of the upper section and drain body

Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
48 658.51	48 658.53	48 658.63	48 658.11	48 658.11
Drainage capacity* 2.2 / 1.3	Drainage capacity* 2.2 / 1.3	Drainage capacity* 2.0 / 1.0	Drainage capacity* 2.0 / 1.0	Drainage capacity* 2.0 / 1.0
48 678.51	48 678.53	48 678.63	48 678.11	48 678.11
Drainage capacity* 2.1 / 1.0	Drainage capacity* 2.1 / 1.0	Drainage capacity* 2.0 / 1.0	Drainage capacity* 2.0 / 1.0	Drainage capacity* 2.0 / 1.0
48 683.51	48 683.53	48 683.63	48 683.11	48 683.11
Drainage capacity* 2.1 / 1.0	Drainage capacity* 2.1 / 1.0	Drainage capacity* 2.0 / 1.0	Drainage capacity* 2.0 / 1.0	Drainage capacity* 2.0 / 1.0
48 611.51	48 611.53	48 611.63	48 611.11	48 611.11
Drainage capacity* 2.2 / 1.0	Drainage capacity* 2.2 / 1.0	Drainage capacity* 2.0 / 1.0	Drainage capacity* 2.0 / 1.0	Drainage capacity* 2.0 / 1.0

* Drainage capacity in l/sec with 20 mm / 10 mm threshold see table