Ecoguss and **Practicus**

Accessories

Extension sections Art. no.

with pressure sealing flange

Compatibility: For combination with drain bodies and extension sections; for floor drain Ecoguss and Practicus

Material: PP



48 403


48 404

System 125

with glue flange with counter flange Compatibility: For combination with drain bodies and extension sections; for floor drain *Ecoguss* and *Practicus*

Material: PP

Material: Polymer



Hygiene and odour stop Art. no. 48 550 Megastop Compatibility: For floor drain *Ecoguss* and *Practicus* Function: Mechanical odour trap inclusive hair filter for KESSEL upper sections, in combination with design cover with Lock & Lift system additional protection against backwater up to 0.1 bar Multistop **Compatibility:** For floor drain *Ecoguss* and *Practicus* 48 500 Function: Odour, foam, rodent and insect stop Note: Not in combination with shower channel upper sections Hair filter Compatibility: For Multistop and floor drain 48 700 Ecoguss and Practicus **Odour trap** Compatibility: For all upper sections System 125, 48 600 sealing water height 50 mm according to norm Note: Not in combination with tileable upper ů120**-**Sludge trap Compatibility: For floor drain *Ecoguss* and *Practicus* 48 168

Fire protection / Passage seal			Outer diameter Ø (mm)	Art. no.	
Fire-Kit	Compatibility: Only for Ecoguss / Practicus drains with vertical outlet and odour trap Function: Fire protection insert DIBt Certification		776 - 24 176 - 1	Ø 58/78/83 Ø 50/75 Ø 110	48 099 48 099 48 100
Quick-Fit with fire protection	Compatibility: Only in combination with Fire-Kit protection insert Function: Passage seal for core drillings with Ecoguss and Practicus drain bodies, vertical outlet DIBt Certification	166-			48 990
Quick-Fit without fire protection	Function: Passage seal for core drillings with <i>Ecoguss</i> and <i>Practicus</i> drain bodies, vertical outlet				48 991