Accessories

Pumpfix S, Universale Plus, The Universal, Practicus and volatile liquid traps

Extension section	ns		Art. no.
with centre flange	Compatibility: For backwater pumping station <i>Pumpfix S</i> Additional function: For installation in waterproof concrete Including sealing set: Counter flange in stainless steel, screwed, elastomer sealing sheet made of NK/SBR Ø 700 mm Extension: Max. 294 mm		830 075
with flange and counter flange	Compatibility: For backwater pumping station <i>Pumpfix S</i> Additional function: For connection to an on-site sealing sheet Inclusive: Gasket Extension: Max. 147 mm (In case of deeper installation ensure maintenance capability!)		830 073
with flange	Compatibility: For backwater pumping station <i>Pumpfix S</i> Additional function: For deeper installation Inclusive: Gasket Extension: Max. 147 mm (In case of deeper installation ensure maintenance capability!)		830 070
with three lateral inlets	Material: PP Inclusive: Lip seal and blind plug Height: 175 mm		48 966
without lateral inlet	Compatibility: For basement drain <i>The Universal</i> and volatile liquid traps Material: PP Inclusive: Lip seal Height: 175 mm		48 988
without lateral inlet	Compatibility: For basement drain <i>Practicus</i> Material: PP Inclusive: Lip seal		48 987
Extension section			Art. no.
with pressure sealing flange and counter flange	Inclusive: Waterproofing layer against ground moisture Height: 150 mm		27 298
Waterproofing membrane	Compatibility: Art. no. 27 298		48 651
2 component adhesive	Compatibility: For gluing of KESSEL waterproofing membranes		48 650