

## Yard drain System 400

for higher load classes



Made in polyethylene. Lateral outlet 2.5°, with odour trap and sludge trap. Water-tight, resistant to aggressive wastewater. With fuel-resistant gaskets. Drainage capacity 4.5 l/sec flow rate.

Installation depth (D) from

580 – 710 mm and

730 – 1080 mm

Installation area 585 × 535 mm

Upper section with slotted cover,

class A (1.5 to.) made of polymer, 400 × 400 mm,

class B (12.5 to.) in cast iron according to EN 124,

400 × 400 mm and class D (40 to.) in cast iron

according to EN 124, 450 × 450 mm for continuous height and level adjustment.



### Installation depth 580 – 710 mm

| Outer diameter Ø (mm) | Art. no. |
|-----------------------|----------|
| Ø 110                 | 851 101A |
| Ø 110                 | 851 101B |
| Ø 110                 | 851 101D |
| Ø 160                 | 851 151A |
| Ø 160                 | 851 151B |
| Ø 160                 | 851 151D |

### Installation depth 730 – 1080 mm

| Outer diameter Ø (mm) | Art. no. |
|-----------------------|----------|
| Ø 110                 | 851 102A |
| Ø 110                 | 851 102B |
| Ø 110                 | 851 102D |
| Ø 160                 | 851 152A |
| Ø 160                 | 851 152B |
| Ø 160                 | 851 152D |




Illustration shows Art. no. 851 102A




Illustration shows Art. no. 851 101A